

1 I claim:

2

3 **1.** A support and enclosure structure for fluorescent light
4 bulbs comprising;

5

6 an elongated, hollow tube having opposite ends, an outer wall and
7 an inner volume;

8

9 at least one ventilation opening extending through said outer wall
10 and permitting air flow between said inner volume of said tube
11 and the surrounding environment for cooling of a fluorescent
12 light bulb held therewithin;

13

14 end cap means mounted on said opposite ends of said tube, said end
15 cap means adapted to engage opposite ends of a fluorescent
16 light bulb and support the fluorescent light bulb within said
17 inner volume of said tube free of contact with said outer wall
18 of said tube; and

19

20 said tube constructed of a generally rigid, at least partially
21 translucent material such that light emitted by a fluorescent
22 light bulb held within said tube generally radiates through
23 said outer wall of said tube into the surrounding environment.

24

25 **2.** The support and enclosure structure for fluorescent light
26 bulbs of claim **1** wherein said hollow tube is generally cylindrical
27 in shape.

28

1 **3.** The support and enclosure structure for fluorescent light
2 bulbs of claim **1** wherein said ventilation opening comprises a
3 longitudinally extended slot formed in said outer wall of said
4 hollow tube.

5
6 **4.** The support and enclosure structure for fluorescent light
7 bulbs of claim **1** wherein said ventilation opening comprises a
8 plurality of holes generally spaced along said hollow tube and
9 extending through said outer wall.

10
11 **5.** The support and enclosure structure for fluorescent light
12 bulbs of claim **1** wherein said end cap means each comprise a
13 generally cylindrical plug having an external diameter
14 approximately equal to or slightly greater than the internal
15 diameter of said hollow tube, said generally cylindrical plug being
16 generally hollow and having an electrode opening extending
17 generally coaxially therethrough, said generally cylindrical plug
18 further including a outer flange operative to prevent said end cap
19 means from overextending into said hollow tube.

20
21 **6.** The support and enclosure structure for fluorescent light
22 bulbs of claim **1** further comprising a wire channel formed in the
23 outer surface of said outer wall of said hollow tube and extending
24 along the length of said hollow tube, said wire channel operative
25 to provide a channel for an electrode wire projecting from a
26 fluorescent bulb housed within said hollow tube to run back along
27 said hollow tube yet be safely retained adjacent said hollow tube
28 to generally prevent accidental damage to an electrode wire.

1 7. The support and enclosure structure for fluorescent light
2 bulbs of claim 1 further comprising mounting end cap means adapted
3 to fit over said end cap means and on to said hollow tube
4 facilitating mounting of said hollow tube within a fluorescent
5 light fixture.

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

1 **8.** A support and enclosure structure for fluorescent light
2 bulbs comprising;
3
4 an elongated, hollow tube having opposite ends, an outer wall and
5 an inner volume;
6
7 at least one ventilation opening extending through said outer wall
8 and permitting air flow between said inner volume of said tube
9 and the surrounding environment for cooling of a fluorescent
10 light bulb held therewithin;
11
12 end cap means mounted on said opposite ends of said tube, said end
13 cap means adapted to engage opposite ends of a fluorescent
14 light bulb and support the fluorescent light bulb within said
15 inner volume of said tube free of contact with said outer wall
16 of said tube;
17
18 mounting end cap means adapted to fit over said end cap means and
19 on to said hollow tube facilitating mounting of said hollow
20 tube within a fluorescent light fixture; and
21
22 said tube constructed of a generally rigid, at least partially
23 translucent material such that light emitted by a fluorescent
24 light bulb held within said tube generally radiates through
25 said outer wall of said tube into the surrounding environment.
26
27 **9.** The support and enclosure structure for fluorescent light
28 bulbs of claim **8** wherein said mounting end caps each further

1 comprise at least one mounting pin and at least one wire slot
2 formed in the side wall of said mounting end cap, said wire slot
3 operative to permit electrical wires to extend therethrough to
4 connect to the fluorescent light bulb held within said tube.

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28